

VARTA: OVER 135 YEARS OF GLOBAL INNOVATION JUST LANDED IN THE U.S.

Clarios, the company behind the brand VARTA, brings a legacy of performance, reliability, and innovation.



Dynamic AGM (Absorbent Glass Mat):

Designed for superior power to support the high electrical demands of modern vehicles, making them ideal for start-stop technology, advanced safety features, entertainment systems, and performance upgrades.

- » Up to 2x the cycle life compared to conventional batteries
- » Certified NON-SPILLABLE, maintenance-free design provides the safest solution
- » Patented grids resist corrosion and deliver superior starting power in cold weather
- » Constructed for greater vibration resistance and enhanced durability



Dynamic SLI (Starting, Lighting, Ignition):

Built to power conventional vehicles with moderate electrical demands and standard accessories. Ideal for long-lasting power, perfect for everyday driving.

- » Designed to meet or exceed Original Equipment (OE) specifications
- » Delivers maximum starting power and Cold Cranking Amps (CCA)
- » Maintenance-free design delivers maximum convenience and long service life



ProMotive Heavy Duty:

Consistent and tough performance that offers dependability and longevity on the job. Exceeding other conventional batteries to get the job done.

- » Anchor bonding locks grid elements in place for improved vibration resistance
- » Impact-resistant polypropylene case with reinforced end wall design
- » Maintenance-free technology



Explore the full VARTA US line-up at
www.varta-automotive.com/en-us

It all starts with  **VARTA**
BY CLARIOS

Dynamic AGM Specifications

Group Size	CCA	Reserve Cap.	Amp Hour	Length x Width x Height (in.)			Weight (lbs)
24F	710	120	70	10 3/4	6 13/16	9	43.0
35	650	100	55	9 1/16	6 15/16	8 7/8	42.0
51R	435	75	41	9 3/8	5 1/16	8 3/4	29.4
65	750	120	68	12 1/16	7 9/16	7 9/16	45.4
H3 / LN0 / 153R	420	60	40	6 15/16	6 15/16	7 1/2	26.9
H4 / LN1 / 140R	570	80	50	8 1/8	6 15/16	7 1/2	34.0
H5 / LN2 / 47	680	105	60	9 9/16	6 15/16	7 1/2	37.9
H6 / LN3 / 48	760	120	70	11	6 15/16	7 1/2	43.5
H7 / LN4 / 94R	850	140	80	12 7/16	6 15/16	7 1/2	49.0
H8 / LN5 / 49	900	160	95	13 15/16	6 15/16	7 1/2	55.7
H9 / LN6 / 95R	950	105	105	15 9/16	6 7/8	7 1/2	64.5
AUX12	180	NA	12	5 7/8	3 7/16	5 1/8	9.2
AUX14	200	NA	14	5 7/8	3 7/16	5 5/8	10.5

Dynamic SLI Specifications

Group Size	CCA	Reserve Cap.	Length x Width x Height (in.)			Weight (lbs)
24	700	130	10 1/4	6 13/16	8 7/8	43.1
24F	750	130	10 3/4	6 13/16	9	44.1
25	550	100	9 1/16	6 15/16	8 7/8	36.0
26	575	90	8 3/16	6 13/16	7 3/4	28.7
26R	575	90	8 3/16	6 13/16	7 3/4	28.7
27	810	160	12 1/16	6 13/16	8 7/8	48.4
27F	710	165	12 1/2	6 13/16	8 15/16	49.0
34	800	110	10 1/4	6 13/16	7 7/8	37.7
35	640	100	9 1/16	6 15/16	8 7/8	37.6
51	500	85	9 3/8	5 1/16	8 3/4	27.6
51R	500	85	9 3/8	5 1/16	8 3/4	27.6
58	550	80	10 1/16	7 3/16	6 15/16	27.9
59	590	100	10 1/16	7 11/16	7 3/4	32.2
65	850	150	12	7 9/16	7 9/16	46.4
75	700	95	9 1/16	7 1/16	7 5/16	33.1
78	800	110	10 1/4	7 1/16	7 5/16	37.3
79	840	140	12 1/16	7 1/16	7 3/8	42.4
86	650	90	9 1/16	6 13/16	8	31.7
96R	590	95	9 1/2	6 15/16	6 15/16	30.3
124R	700	120	10 3/8	7	8 5/8	38.9
151R	370	57	7 7/16	4 15/16	8 7/8	22.5
H4 / LN1 / 140R	480	75	8 1/8	6 15/16	7 1/2	27.2
H5 / LN2 / 47	650	100	9 9/16	6 15/16	7 1/2	32.9
H6 / LN3 / 48	750	120	11	6 15/16	7 1/2	38.9
H7 / LN4 / 94R	800	140	12 7/16	6 15/16	7 1/2	42.9
H8 / LN5 / 49	850	150	13 15/16	6 15/16	7 1/2	47.1
T4 / LBN1 / 99R	470	70	8 1/8	6 15/16	6 15/16	29.7
T5 / LBN2 / 90	650	90	9 9/16	6 15/16	6 15/16	31.6
V4 / 102R	520	50	8 1/8	6 15/16	5 1/2	22.7

ProMotive Heavy Duty Specifications

Group Size	CCA	Reserve Cap.	Length x Width x Height (in.)			Weight (lbs)
31	950	195	13	6 13/16	9 7/16	59.9
31P	950	195	13	6 13/16	9 7/16	60



Explore the full VARTA US line-up at
www.varta-automotive.com/en-us

It all starts with  **VARTA**
BY CLARIOS